


**PRODECOR T** Aluminium anodised – chrome-plated

**Joint-end cover profiles**



**Fields of application:**

PRODECOR T joint-end cover profile is a T-shaped profile that can be inserted retroactively in an open joint to form a transition between coverings of the same height.

The design of PRODECOR T joint-end cover profiles is adapted to the coverings in such a way that, with a high level of application safety during installation, they cover the joint reliably and with lasting effect and protect edges of the covering material against mechanical damage.

Typical areas of application in internal domestic areas are:

- Creating transitions (also retroactively) in floors/walls and coverings that join each other, such as tiles, natural stone, parquet or laminate and similar.
- Decorative element in wall and floor areas
- For concealing joints of different widths

**Product advantages:**

PRODECOR T joint-end cover profiles are easy to fit. When fitted, they rise minimally above the covering surface. This makes it possible to specifically achieve accentuated spatial creations. The different widths and the elegant surface finish can be allocated to a wide variety of coverings. PRODECOR T joint-end cover profiles can also be fitted in an open joint after the coverings have been installed.

**Specifications:**

Material Aluminium	anodised	chrome-plated
Length [m]	2.50 / 2.70	2.50
Face widths [mm]	14 / 20 / 25	14 / 25

For details, see latest price list.

**Delivery form:**

Anodised aluminium	Package wrapped completely with stretch film, packed in a dispatch box
Chrome plated aluminium	Profiles wrapped with protective film, bound at the ends with stretch film, packed in a dispatch box
10 profiles	1 package
Packaging unit	10 / 40 items
Customs tariff number for anodised aluminium: 76061220	
chrome plated aluminium: 76042990	

For the latest order quantities (KA) and packaging units (VPE), please refer to the price list, the relevant price sheets or product news sheets, or speak to your specialist dealer.

**Storage and transportation:**

Store and transport in dry areas that are protected against dirt, impact, abrasion and other foreign matter. To avoid any risk of deformation, do not place any load on the profiles and preferably store in the lying position. Protect foil-wrapped profiles from sunlight / UV rays.

# PRODECOR T Aluminium anodised – chrome-plated

## Disposal:

Profiles that have been cleaned of foreign matter can be disposed of in a metal recycling container. Observe local authority regulations respectively.

## Thermal degradation:

No degradation if used in the correct manner.  
Avoid excessive heat.

## Processing:

### Preparatory measures:

The coverings that join each other must be sturdy, dry, level, straight, flush and/or horizontal, free of parting agents and solvents and suitable for the planned bonding and sealing compounds.

The joint to be covered must have a minimum depth of 9 mm and be free of all contamination that would impair effective bonding (e.g. dust, oil, grease).

It is recommended that the profile is cleaned of any grease and dirt (if present) before installation using suitable cleaners.

### Installation:

Use only undamaged profiles. Remove any protective film from the visible sides of the profiles before fitting.

To cut to the required length, use suitable clamps, saws or cutting devices as well as personal protective equipment. Deburr the edges using a suitable tool.

Using suitable, pH-neutral sealing and filling compounds that allow the requisite amount of movement (e.g. neutral cross-linked silicon, MS polymer; acrylic, ...), fill the cleaned joint chamber to the height of the covering up to 50-75%. Use backfill cord if necessary.

Apply a fine bead of modelling silicon or acrylic straightaway to the left and right of the lip on the underside of the PRODECOR T joint-end cover profile.

Then immediately insert the profile in the filled joint with the vertical lip. The silicon or acrylic that escapes under the profile must be wiped away cleanly and the edges must be smoothed off using a suitable smoothing agent or the adjacent surfaces and the upper side of the profile should be masked off in advance to protect against soiling. Ensure that the side flanks of the profiles rest completely against the edges of the covering.

## Cleaning:

Use clean water, pH-neutral cleaning agent, a sponge or cleaning cloth.

Ensure that there is no sanding or grinding effect.

If necessary, use an alcohol-based cleaner or a cleaner especially developed for chrome-plated or anodised surfaces.

Perform routine cleaning regularly in accordance with local conditions.

## Chemical and physical resilience:

Before using cleaning agent or collected water, check whether it has a corrosive or damaging effect on the profiles. This also applies to correct dosage during use.

Never use agents containing hydrochloric or hydrofluoric acid.

Any contact with chlorine bleaching agents, cement residue cleaners, strong acids or alkaline should be avoided.

Anodised profiles react sensitively to potent alkaline media.

Substances containing cement or lime in combination with water can alter the surface depending on the solution and time allowed to take effect. Always remove grout and joint compound immediately from the sides on display or mask off the visible sides to protect them.

Once the adhesive, grout and filling compound is dry, the profile can take mechanical loads as per its intended use.

Abrasive influences or the use of equipment or execution of activities on the profile with damaging effect should be avoided as a rule.

Check cleaning tools and equipment with bristles and abrasive polishing pads to see if they scratch the surface.

# PRODECOR T Aluminium anodised – chrome-plated

## Standards and regulations:

*In addition to the observation and consideration of relevant specialist rules, standards and generally recognised rules of technology, attention is drawn in particular to the following regulations:*

- ATV DIN 18352 Tile laying work
- ATV DIN 18332 Natural stone work
- ATV DIN 18157 Fitting ceramic trim using thin-bed method
- ATV DIN 18202 'Tolerances in surface construction'
- ZDB bulletin 'Expansion joints' (last version)
- ZDB bulletin 'Flooring/covering subjected to high loads' (last version)

## Important information:

- In conjunction with the profiles, use only neutrally cross-linked silicon.
- The production processes necessitate a certain play of colours between the individual profiles and their appearance is subject to the characteristic, industrial processes during manufacture.
- Protect any existing film against sunlight and UV light protection and remove completely before fitting.

All information, references, instructions, basic engineering principles, regulations, standards and expertise are based on German and largely equivalent European regulations and training standards, irrespective of additional country-specific supplements and amendments.

All our specifications are based on our experience and careful analysis. We are unable to examine or influence the diversity of associated materials used and the various construction site and processing conditions in detail. The quality and function of your work is therefore dependent on your professional construction site evaluation and utilisation of the products. In case of doubt, carry out your own tests or seek technical application advice. Please refer to the laying and processing guidelines of the floor covering manufacturers or the manufacturers of associated products. All previously published product data sheets cease to apply on publication of this product data sheet.

© Proline Systems 2016 – We grant our customers the permission of reproduction and transfer to their customers, provided that clear reference is made to our copyrights. All other rights reserved.